



DESCRIPTION

ADHL-LAB-LINER is an elastomeric polyurethane with a high solids component for outdoor and indoor use. Contains rubber granules that provides a non-slip surface.

BENEFITS

- Excellent flexibility.
- Good adhesion to metal/iron.
- Good abrasion resistance.
- Excellent resistance to low temperatures.
- High rate of solids.
- Easy to use.
- Contains recycled rubber granules.

HANDLING PROPERTIES

| | |
|---|------------|
| Recommended thickness | 20-30 mils |
| Packing unit litres / gal us | 3.78 / 1 |
| Viscosity (mixed),..... | 70-90 ku |
| Solids (by weight) | 70+/-2% |
| Drying time 2-8 hours | |
| Solids by volume | 70+/-2% |
| Dust-free 24-48 hours, hard depending on humidity | |
| Color on application | Black |

COVERAGE

THEORETICAL COVERAGE 1 MIL: 1122 SQUARE FEET / GALLON

10 degrees Celsius: 14-18 hours min

Maximum 2 months

VISCOSITY

70-90 km

Recommended thinner

UC-502 10% maximum

LIMITATIONS

- Protect from moisture.
- Do Not Use in a soaked environment.
- To get a good hardening of the relative humidity needed from 40% or more.

- Once the product is opened, the product should be used the same day.
- Store in a dry place.
- 12 months shelf life.

AREA PREPARATION

Prepare the surface beforehand, remove dirt, solubles, dust, oil, grease, chalking or contaminant. Sand the surface on which the coating will be applied to leave no marks. Sand blasting residues should be vacuumed or blown. Wash the surface to be painted with a solvent such as xylene or acetone and allow sufficient time for drying (Usually 2-8 hours). Apply the ADHL-LAB-LINER with a roller or brush. Mixing the product during application may be necessary to keep the rubber particles in suspension and ensure uniform application.

HEALTH AND SECURITY

In case of skin contact, wash with water and soap. In case of contact with eyes, rinse immediately with water for at least 15 minutes. Communicate with a doctor. Avoid contact with skin, eyes, and mouth. Also avoid breathing vapours. Wear protective goggles and chemical resistant gloves. The use of a NIOSH / MSHA filtered respirator is recommended. Provide adequate ventilation. For more information, see the Material Safety Data Sheet.

SHELF LIFE

12 months in its original packaging, unopened.

(Please note that the indicated gallon yield is calculated for flat surfaces. If the surface is porous or imperfect, it will be necessary to cover the same surface.)*

SAFETY PRECAUTIONS

Consult the Material Safety Data Sheet (MSDS) for specific instructions.

WARRANTY

The recommendations made and the information here in is the result of accurate laboratory and field tests under controlled conditions. We guarantee that the quality and properties of the materials supplied conform to our standards. Adhesiveslab Products, makes no warranties, expressed or implied, as uses and applications are beyond our control. Adhesiveslab Products. shall not be liable for any injury, loss, or damage (direct or consequential) arising from use or inability to use the products. Before using, the user is urged to pre-test the products in his/her own environment to determine the suitability of the products for their intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Adhesiveslab Product's liability, if any, is limited to a refund of the purchased price or replacement of that portion of the merchandise proven to be defective. Adhesiveslab Products shall have no other liability, including liability for incidental, consequential or result- ant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

This warranty may not be modified or extended by representatives of Adhesiveslab Products, it's distributors or dealers."