



DESCRIPTION

LABCRETE-PRIMER is a liquid bonding agent for use with LABCRETE-SELF.

WHERE TO USE

Used as a bonding agent, LABCRETE-PRIMER permits direct application of LABCRETE-SELF to structurally sound surfaces.

BENEFITS

- Bond is stronger than most concrete
- Low viscosity to penetrate and seal surface
- Prevents air voids from forming in LABCRETE-SELF

PROPERTIES

Type: vinyl acetate polymer. Not affected by alkalinity of lime or Portland cement.

APPLICATION

Surface must be structurally sound, free of dirt, grease, oil, etc. After diluting LABCRETE-PRIMER with water and mixing completely, it should be broomed into the surface to be topped. Broom out puddles. The primer should be completely dry before the topping is applied. In any case it should be kept free of all traffic and topped within 24 hours.

LIMITATIONS

- protect from freezing
- do not apply when temperature is below 7°C (45°F)
- do not use as a bonding agent in areas subject to constant water exposure or immersion

COVERAGE

LABCRETE-PRIMER is mixed with water at a ratio of 1 part LABCRETE-PRIMER to 2 parts potable water (by volume). 3.8L (1 U.S. gallon) of diluted LABCRETE-PRIMER will cover approximately 9.29-11.6 m² (100-125 112). For porous concrete it may be necessary to apply a second coat.

PACKAGING

18.9L (5 U.S. gal) - 23 kg (51 lb)
3.79L (1 U.S. gal) - 4.3 kg (9.5 lb)
1L (0.26 U.S. gal) - 1.2 kg (2.6 lb)

STORAGE

Do not freeze. Store in a heated warehouse above 4.5°C (40°F).

SHELF LIFE

One year from date of manufacture when stored in original unopened container, and under normal warehouse conditions.

SAFETY PRECAUTION

Consult Safety Data Sheet for specific instructions.

WARRANTY

The recommendations made and the information here in is the result of accurate laboratory and field tests under controlled conditions. We guarantee that the quality and properties of the materials supplied conform to our standards. Adhesiveslab Products, makes no warranties, expressed or implied, as uses and applications are beyond our control. Adhesiveslab Products. shall not be liable for any injury, loss, or damage (direct or consequential) arising from use or inability to use the products. Before using, the user is urged to pre-test the products in his/her own environment to determine the suitability of the products for their intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Adhesiveslab Product's liability, if any, is limited to a refund of the purchased price or replacement of that portion of the merchandise proven to be defective. Adhesiveslab Products shall have no other liability, including liability for incidental, consequential or result- ant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

This warranty may not be modified or extended by representatives of Adhesiveslab Products, it's distributors or dealers."