

IDENTIFICATION

PRODUCT NAME: ADHL-MC WATERBASED EPOXY PRIMER - **PART A**

MANUFACTURER/SUPPLIER: Adhesiveslab 235 Rayette Rd, Unit #4 Concord, Ontario Canada L4K 2G1 24
HOUR EMERGENCY NUMBER: 1-800-340-7697
APPLICATION AND USE: Two-component waterborne primer and sealer (water based dispersion).
PRODUCT DESCRIPTION: MC Waterbased Epoxy Primer – Part A

HAZARDS IDENTIFICATION

GHS CLASSIFICATION

- Acute toxicity (oral): Category 2
- Skin corrosion/irritation: Category 2
- Skin sensitization: Category 1
- Chronic aquatic toxicity: Category 2

SIGNAL WORD
WARNING



HAZARD STATEMENTS

- H317 May cause an allergic skin reaction

PRECAUTIONARY STATEMENTS

PREVENTION

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves/protective clothing/eye protective/face protection

RESPONSE

- P302 + P352 IG ON SKIN: Wash with plenty of water
- P333 + P313 If skin irritation or a rash occurs: Get medical advice/attention
- P362 +P364 Take off contaminated clothing and wash before reuse

STORAGE

- P403 + P233 Store in a well ventilated place. Keep container tightly closed.

DISPOSAL

- P501 Dispose of contents/container in accordance with local/regional/national/ international regulation.

In case of Fire:

Notify your local fire station and inform the location of the fire and characteristics hazard.
Wear appropriate protective equipment

First Aid

- P301 + P312: IF Swallowed: Call a POISON CENTRE or doctor/physician if you feel unwell.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Other hazard which do not result in classification: (NFPA Classification)

o NFPA grade (0~4 level)

- Health: 2 Flammability: 1, Reactivity : 0

WHMIS 1988 Classification (Canada):

Class D, Division 2, Subdivision B: irritant

TRANSPORTATION OF DANGEROUS GOODS INFORMATION:

Not Regulated

COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	C.A.S. #	Weight
Oxirane, 2-2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis-, homopolymer	25085-99-8	50%-60%
Water	15625-89-5	40%-50%

SAFETY DATA SHEET

FIRST-AID MEASURES

EYE CONTACT

- Do not rub your eyes.
- Flush eyes immediately with large amounts of running water for at least 15 minutes while holding eyelids open until irritation subsides.
- Do not attempt to neutralize with chemical agents. Obtain medical attention immediately.

SKIN CONTACT

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Go to the hospital immediately if symptoms (flare, irritate) occur.

- Wash thoroughly after handling.
- Wash immediately with plenty of soap and water. Remove and clean all contaminated clothing and laundry before reuse.

INHALATION

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- In the case of overexposure, remove to fresh air. Get medical attention if the victim is in respiratory distress.

INGESTION

- About whether I should induce vomiting Take the advice of a doctor
- Rinse your mouth with water immediately.
- If swallowed, drink two glasses of water. Do not induce vomiting. The material is corrosive. Do not give anything to mouth to an unconscious person. Get prompt medical attention.

DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE

- Not available

NOTES TO PHYSICIAN

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

UNSUITABLE EXTINGUISHING MEDIA

- Avoid use of water jet for extinguishing

SPECIAL PROTECTION EQUIPMENT FOR FIRE FIGHTERS

- Notify your local fire-station and inform the location of the fire and characteristics hazard.
- Using an unattended and water devices in case of large fire and leave alone to burn if you do not imperative.
- Avoid inhalation of materials or combustion by-products. -Do not access if the tank on fire.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Keep containers cool with water spray.
- Vapour or gas is burned at distant ignition sources can be spread quickly.

GENERAL FIRE HAZARDS

- Combustible liquid; may release vapours that form combustible mixtures at or above the flash point. Toxic gases will form upon combustion.

FIRE FIGHTING

-Wear NIOSH-approved self-contained breathing apparatus with independent air supply. Wear complete body protective butyl rubber clothing. Personnel in vicinity and downwind should be evacuated.

HAZARDOUS COMBUSTION PRODUCTS

-Carbon dioxide, and carbon monoxide, various hydrocarbons, phenol.

ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

- Must work against the wind, let the upwind people to evacuate
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak
- Avoid skin contact and inhalation.

ENVIRONMENTAL PRECAUTIONS

- Prevent runoff and contact with waterways, drains or sewers
- If large amounts have been spilled, inform the relevant authorities.

CONTAINMENT AND CLEAN UP

- Large spill: stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent
- Dike for later disposal.
- Prevent the influx to waterways, sewers, basements or confined spaces.

PROCEDURE IN CASE OF LEAKS

Prevent spills from entering sewers, watercourses or low areas. Absorb with sand or other absorbent material. Residue may be removed with hot water and detergent. All precautions should be taken when cleaning the spill with solvent.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge to sewers or waterways. Marine Pollutant (Very toxic to aquatic organisms)

SPILL CONTROL AND DISPOSAL

Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.

HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Wash thoroughly after handling

- Avoid direct physical contact
- Avoid contact with incompatible materials.
- Refer to Engineering controls and personal protective equipment.
- Do not inhale the steam prolonged or repeated.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Do not inhale the steam prolonged or repeated.
- Do not use damaged containers
- Do not apply direct heat
- Save applicable laws and regulations.
- Avoid direct sunlight
- Keep in the original container.
- Collected them in sealed container.
- Do not eat, drink or smoke when using this product.
- Store away from water and sewer.

HANDLING STORAGE AND SHIPPING

Keep container closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. Do not handle or store near an open flame, sources of heat, or sources of ignition. Protect material from direct sunlight. This product will accumulate static charges which may cause an incendiary electrical discharge. Use proper grounding procedures. Empty product containers may contain product residue. DO NOT REUSE.

EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

OSHA PEL

- Not available

ACGIH TLV

- Not available

DIPROPYLENE GLYCOL METHYL ETHER

- Not available

APPROPRIATE ENGINEERING CONTROL

- A system of local and/or general exhaust is recommended to keep employee exposure above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

PERSONAL PROTECTIVE EQUIPMENT

EYE / TYPE

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

RESPIRATORY PROTECTION

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapour cartridge(s).
- Any chemical cartridge respirator with a full face-piece and an organic vapour cartridge(s).
- Any air-purifying respirator with a full face-piece and an organic vapour canister.
- For unknown Concentration or Immediately Dangerous to Life or Health: Any supplied-air respirator with full face-piece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full face-piece.

SKIN PROTECTION/ GLOVES/ CLOTHING

- Wear appropriate clothing

OTHER/TYPE

- Not available

PERSONAL PROTECTION

The selection of personal protective equipment varies depending upon conditions of use. When handling product wear long sleeves, chemical resistant gloves and safety glasses with side shields. Where splashing during mixing may occur wear full face shield. Where concentrations in air may exceed the occupational exposure limits and where engineering work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation. The respirators may not be necessary for handling the materials in outdoor environment. Eye wash station (sink) or shower facility near the job is recommended in case of emergency.

Effect of Overexposure

INHALATION

Do not heat the material. Vapours or mist generated from heating the material or as from exposure in poorly ventilated areas are irritating and cause nasal discharge. Coughing and discomfort in nose and throat. Prolonged or repeated overexposure may result in lung damage.

EYES

Cause irritation, experienced as pain, with excess blinking and tear production, and seen as extreme redness and swelling of the eye and chemical burns of the eye.

SKIN

Causes severe skin irritation with pain, excess redness and swelling with chemical burns. It may cause skin sensitization. Other than the potential skin irritation, effects noted above acute (short term) adverse effects are not expected from brief skin contact.

INGESTION

Acute (brief exposure): Low toxicity causes irritation. Chronic (prolonged exposure): causes burning of mouth, throat, and stomach with abdominal and chest pain, nausea, vomiting, diarrhea, thirst and weakness.

INGESTION: CHRONIC: Refer to acute ingestion.

Toxic effects or reproduction: No

Teratogenicity: No

Mutagenicity: No
Carcinogenicity: No

Acute or chronic exposure should be avoided as it will increase the toxicological problems mentioned in this section and may aggravate respiratory problems. Repeated skin contact may cause a persistent irritation or dermatitis. Repeated inhalation may cause lung damage.

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Specific Gravity: 1.07 @ 23°C (73°F)
Solubility in Water: Soluble
Boiling Point: 100°C
Freezing/Melting Point: n/av
Viscosity: 2,200 cps @ 23°C (73°F)
Evaporation Rate: water
Volatile (voc): None
Vapour Density: n/av
Odour: Negligible
Appearance: Clear liquid

STABILITY AND REACTIVITY

REACTIVITY

-This material is stable under recommended storage and handling conditions.

CHEMICAL STABILITY

-This material is stable under recommended storage and handling conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: CONDITIONS TO AVOID

- Hazardous Polymerization will not occur.
- Avoid contact with incompatible materials and condition.
- Avoid: Accumulation of electrostatic charges, Heating, Flames and hot surfaces.

INCOMPATIBLE MATERIALS

-Not available

HAZARDOUS DECOMPOSITION PRODUCTS

-May emit flammable vapour if involved in fire.

TOXICOLOGICAL INFORMATION

Acute Toxicity

Ingestion: No data is available on the product itself
Ingestion – Components: N/A

Inhalation: No data is available on the product itself
Inhalation – Components: N/A

Dermal: No data is available on the product itself Dermal – Components: N/A

Sensitization:

May cause sensitization of susceptible persons by skin contact. Did not cause allergic skin reactions when tested in mice.

Skin Corrosion/Irritation: Extremely corrosive and destructive to tissue

Serious eye damage/eye irritation: May cause irreversible eye damage

Respiratory or skin sensitization: N/A Germ Cell Mutagenicity: N/A

Carcinogenicity: N/A Reproductive toxicity: N/A

ECOLOGICAL INFORMATION

Aquatic toxicity: no data available

Persistence and degradability: no data available

Additional to ecological information

Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterway, drains and sewers.

TRANSPORTATION INFORMATION

Domestic/International Regulation

TDG

Not Regulated

IMDG

Not Regulated

IATA

Not Regulated

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

IDENTIFICATION

PRODUCT NAME: DHL-MC WATERBASED EPOXY PRIMER - **PART B**

MANUFACTURER/SUPPLIER: Adhesiveslab 235 Rayette Rd, Unit #4 Concord, Ontario Canada L4K 2G1 24
HOOR EMERGENCY NUMBER: 1-800-340-7697
APPLICATION AND USE: Two-component waterborne primer and sealer (water based dispersion).
PRODUCT DESCRIPTION: MC Waterbased Two-component waterborne primer and Sealer (Polyamine Emulsion) PART -B

HAZARDS IDENTIFICATION

GHS CLASSIFICATION

- Acute toxicity (oral): Category 4
- Skin corrosion/irritation: Category 4
 - Skin sensitization: Category 1B
 - Serious Eye Damage: Category 1
 - Reproductive toxicity: Category 2

SIGNAL WORD WARNING



HAZARD STATEMENTS

- H302+H312 Harmful if swallowed or in contact with skin
- H314 Causes severe skin burns and eye damage 12
- H317 May cause an allergic skin reaction
- H335: May cause respiratory irritation

PRECAUTIONARY STATEMENTS

PREVENTION

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood.

- P260 Do not breathe dust/fume/gas/mist/vapours/spray
- P264 Wash hands thoroughly after handling
- P270 Do not eat, drink, or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves/protective clothing/eye protective/face protection
- P284 Wear respiratory protection.

RESPONSE

- P301+P330+P331: IF SWALLED: rinse mouth. DO NOT induce vomiting.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P304+P340+P310: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
- P305+P351+P338+P310: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Immediately call a POISON CENTRE/doctor.
- P308+P313: IF exposed or concerned: Get medical advice/attention
- P333+P313: If skin irritation or rash occurs: Get medical advice/attention
- P363+P364: Take off contaminated clothing and wash before reuse

STORAGE

- P403 + P233 Store in a well ventilated place. Keep container tightly closed.

DISPOSAL

- P501 Dispose of contents/container in accordance with local/regional/national/ international regulation.

IN CASE OF FIRE

- Notify your local fire station and inform the location of the fire and characteristics hazard.
- Wear appropriate protective equipment

WHMIS Classification (Canada): Class D, Division 2, Subdivision B TRANSPORTATION OF DANGEROUS GOODS INFORMATION: Not Regulated

COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	C.A.S. #	Weight
Poly aminomethylethoxy	9046-10-0	1-10
1-phenoxy-2-propanol	107-98-2	1-5
Dipropylene Glycol Butyl Ether	29911-28-2	1-5
2- Methoxymethylethoxypropanol	252-104-2	1-5
Propan-2-ol, 1-methoxy	107-98-2	1-3
Benzyl alcohol	100-51-6	1-3

SAFETY DATA SHEET

FIRST-AID MEASURES

EYE CONTACT

- Do not rub your eyes.
- Flush eyes immediately with large amounts of running water for at least 15 minutes while holding eyelids open until irritation subsides.
- Do not attempt to neutralize with chemical agents. Obtain medical attention immediately.

SKIN CONTACT

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Go to the hospital immediately if symptoms (flare, irritate) occur.
- Wash thoroughly after handling.
- Wash immediately with plenty of soap and water. Remove and clean all contaminated clothing and launder before reuse.

INHALATION

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- In the case of overexposure, remove to fresh air. Get medical attention if the victim is in respiratory distress.

INGESTION

- About whether I should induce vomiting Take the advice of a doctor
- Rinse your mouth with water immediately.
- If swallowed, drink two glasses of water. Do not induce vomiting. The material is corrosive. Do not give anything to mouth to an unconscious person. Get prompt medical attention.

ADDITIONAL INFORMATION

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

MOST IMPORTANT SYMPTOMS/ EFFECTS, ACUTE OR DELAYED

- Not available.

FIRE-FIGHTING MEASURES

GENERAL FIRE HAZARDS

- Combustible liquid; may release vapours that form combustible mixtures at or above the flash point. Toxic gases will form upon combustion.

SUITABLE EXTINGUISHING MEDIA

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

UNSUITABLE EXTINGUISHING MEDIA

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

SPECIAL PROTECTION EQUIPMENT FOR FIRE FIGHTERS

- A face shield should be worn
- Use personal protective equipment
- Wear self contained breathing apparatus for fire fighting if necessary

HAZARDOUS COMBUSTION PRODUCTS

-Carbon dioxide, and carbon monoxide, various hydrocarbons, phenol.

Flashpoint and Method: 75 °C (T.C.C.)

Auto ignition Temperature: 350°C

Flammable Limits: 1.1 - 7% by volume

ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

- Must work against the wind, let the upwind people to evacuate
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak
- Avoid skin contact and inhalation.

ENVIRONMENTAL PRECAUTIONS

- Prevent runoff and contact with waterways, drains or sewers
- If large amounts have been spilled, inform the relevant authorities.

CONTAINMENT AND CLEAN UP

Large spill: stay upwind and keep out of low areas. Dike for later disposal.

- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent
- Dike for later disposal.
- Prevent the influx to waterways, sewers, basements or confined spaces.

PROCEDURE IN CASE OF LEAKS

Extinguish and eliminate source of ignition until area is determined to be free from explosion or fire hazards. Prevent spills from entering sewers, watercourses or low areas. Absorb with sand or other absorbent material (do not use sawdust). Residue may be removed with hot water and detergent. Flush small spills with water.

HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

- Wash thoroughly after handling

- Avoid direct physical contact
- Avoid contact with incompatible materials.
- Refer to Engineering controls and personal protective equipment.
- Do not inhale the steam prolonged or repeated.

CONDITIONS FOR SAFE STORAGE

- Do not use damaged containers
- Do not apply direct heat
- Save applicable laws and regulations.
- Avoid direct sunlight
- Keep in the original container.
- Collected them in sealed container.
- Do not eat, drink or smoke when using this product.
- Store away from water and sewer.

EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

DIPROPYLENE GLYCOL METHYL ETHER

- Not available

APPROPRIATE ENGINEERING CONTROL

- During spraying, wear suitable respiratory equipment. Wear appropriate respirator when ventilation is inadequate
- Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates that is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

PERSONAL PROTECTIVE EQUIPMENT

EYE / TYPE

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

RESPIRATORY PROTECTION

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapour cartridge(s).
- Any chemical cartridge respirator with a full face-piece and an organic vapour cartridge(s).
- Any air-purifying respirator with a full face-piece and an organic vapour canister.
- For unknown Concentration or Immediately Dangerous to Life or Health: Any supplied-air respirator with full face-piece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full face-piece.

SKIN PROTECTION/ GLOVES/ CLOTHING

- Wear appropriate clothing

OTHER/TYPE

-Not available

PERSONAL PROTECTION

The selection of personal protective equipment varies depending upon conditions of use. When handling product wear long sleeves, chemical resistant gloves and safety glasses with side shields. Where splashing during mixing may occur wear full face shield. Where concentrations in air may exceed the occupational exposure limits and where engineering work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation. The respirators may not be necessary for handling the materials in outdoor environment. Eye wash station (sink) or shower facility near the job is recommended in case of emergency.

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Specific Gravity: 1.08 @ 23°C (76°F)
Vapour Pressure: 18.7 mmHg @ 23°C (76°F)
Solubility in Water: Dispersible
Boiling Point: >96°C
Freezing/Melting Point: 0°C
Viscosity: 400 cps 23°C (73°F)
Vapour Density: >1
Evaporation Rate: n/av
Volatile: (voc): 50%
Odour: Slight
Appearance: Milky liquid
Hazardous Air Pollutant: None

STABILITY AND REACTIVITY

REACTIVITY

-This material is stable under recommended storage and handling conditions.

CHEMICAL STABILITY

-This material is stable under recommended storage and handling conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: CONDITIONS TO AVOID

- Hazardous Polymerization will not occur.
- Avoid contact with incompatible materials and condition.
- Avoid: Accumulation of electrostatic charges, Heating, Flames and hot surfaces.

INCOMPATIBLE MATERIALS

- Avoid contact with strong oxidizing agents.
- Avoid extremely reactive or incompatible with the following materials: acids, ammonia, carbon monoxide, carbon dioxide, aldehydes, ketones.

HAZARDOUS DECOMPOSITION PRODUCTS

- May emit flammable vapour if involved in fire.

Decomposition products may include the following materials:

- Carbon dioxide
- Carbon monoxide
- Nitrogen oxides
- phenol

TOXICOLOGICAL INFORMATION

Ingestion: No data is available on the product itself

Ingestion – Components:

-Poly aminomethylethoxy	LD50: 2,880 mg/kg Species: Rat
-Propan-2-ol, 1-methoxy	LD50: 5,700 mg/kg Species: Rat
-Dipropylene Glycol Butyl Ether	LD50: 4,400 mg/kg Species: Rat
-Benzyl alcohol	LD50: 1,230 mg/kg Species: Rat

Inhalation: No data is available on the product itself

Inhalation – Components:

-Benzyl alcohol	LD50 (4 h): >4.178 mg/L Species: Rat
	OCED Test Guideline 403

Dermal: No data is available on the product itself

Dermal – Components:

-Poly aminomethylethoxy	LD50: 2,980 mg/kg Species:Rabbit
-Propan-2-ol, 1-methoxy	LD50: 13,000 mg/kg Species: Rabbit
-Dipropylene Glycol Butyl Ether	LD50: >2,000 mg/kg Species:Rabbit
-Benzyl alcohol	LD50: 2,000 mg/kg Species: Rabbit

SENSITIZATION

May cause sensitization of susceptible persons by skin contact. Did not cause allergic skin reactions when tested in mice.

Skin Corrosion/Irritation

Extremely corrosive and destructive to tissue

Serious eye damage/eye irritation: May cause irreversible eye damage Respiratory or skin sensitization
N/A

Germ Cell Mutagenicity

N/A

Carcinogenicity

N/A

Reproductive toxicity

N/A

ECOLOGICAL INFORMATION

AQUATIC TOXICITY

-No data available

PERSISTENCE AND DEGRADABILITY

-No data available

TRANSPORTATION INFORMATION

Domestic/International Regulation

TDG

Not Regulated

IMDG

Not Regulated

IATA

Not Regulated

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.